

## Series 8400 Door Protection Plates





.050" Thickness

### Features:

- Door Protection Plates are fabricated from the finest architectural aluminum, brass, and stainless steel, or 1/8" thick clear acrylic plastic or black or brown high impact polyethylene.
- All aluminum, brass, bronze and stainless steel Door Protection Plates meet ANSI A156.6 requirements for .050" thickness.
- Optional Beveling—For beveling of top and two sides of plates suffix with B3E, and for beveling of four sides suffix with B4E. Plastic plates are beveled on all four sides as standard.
- Each plate is packaged carefully wrapped in strong kraft paper with #6 x 5/8" oval head, undercut sheet metal screws plated to match, for easy installation on hollow metal, laminate, or wood doors. All plates are packaged in heavy duty corrugated cardboard; larger plates are enclosed in a wooden frame.



- Use No. 8401 Kickplate Gasket Tape as a buffer between brass kickplates and metal doors to help prevent tarnishing which may result from electrolytic oxidation. One package provides enough double-sided adhesive-backed foam tape for the perimeter of an 8" x 34" plate.
- Finishes:  
Brass: B3, B4, B5, B10, B10B (for heights over 24", check with customer service)  
Stainless Steel: S32D, S32  
Aluminum: PA28  
Plastic: BLK, BRN, CLR

 <p><b>Mop Plates</b></p> <ul style="list-style-type: none"> <li>• Protect the bottom of the pull side of door subject to cleaning and mopping procedures.</li> <li>• Size Ranges: 4" to 6" high, 22" to 48" wide</li> </ul>	 <p><b>Kick Plates</b></p> <ul style="list-style-type: none"> <li>• Protect the bottom of the push side of doors subject to scuffing from foot traffic.</li> <li>• Recommended for all doors subject to normal use (especially doors using a closer).</li> <li>• Size Ranges: 8" to 24" high, 22" to 48" wide</li> </ul>	 <p><b>Stretcher Plates</b></p> <ul style="list-style-type: none"> <li>• Protect doors at specific areas where consistent contact is made by stretchers, service carts or other equipment.</li> <li>• Usually applied to push side of doors.</li> <li>• Specify "B4E" Option for beveled edges.</li> <li>• Size Ranges: 6" to 8" high, 22" to 48" wide</li> </ul>	 <p><b>Armor Plates</b></p> <ul style="list-style-type: none"> <li>• Protect lower half of doors from abuse by hard carts, trucks and rough usage.</li> <li>• Usually applied to push side of single doors and both sides of double acting doors.</li> <li>• Size Ranges: 26" to 48" high, 22" to 48" wide</li> </ul>
---	---	---	--

## 8400 KICK PLATE

### A. ~~RL30~~ Roller Latch

Brass or bronze units feature silent rubber roller (nylon or nylon-covered brass rollers optional) and are available with standard 2-1/4" (57.2mm) x 1-11/16" (42.9 mm) stile or 4-7/8" (123.8 mm) ASA stile (suffix A). Projection of roller is easily adjusted by way of adjusting screws on face of unit.



**A**

## ZRL30 ROLLER LATCH

## IVES HARDWARE PRODUCTS

APPENDIX B

HARDWARE ILLUSTRATION # 012A

---

WS407CCV	Screw, Drywall Anchor	2-1/2"	3/8"	1"
----------	--------------------------	--------	------	----

---



WS407CCV

WS407CCV WALL STOP

**IVES HARDWARE PRODUCTS**

APPENDIX B

HARDWARE ILLUSTRATION # 012B